



CONSULATE GENERAL OF INDIA
No. 4 Myin Pying Kwin Street
Pyi Daw Thar Quarter
Sittwe Township, Myanmar
Tel: (0095) 43 2022918-19, 2022076
Fax: (0095) 43 2022917
Email: hoc.sittwe@mea.gov.in
adm.sittwe@mea.gov.in

No. Sit/Adm/885/04/2017

June 05, 2018

Notice Inviting Tender

Subject: Supply and installation of Closed Circuit Television (CCTV) Cameras at the Consulate General of India, Sittwe

The Consulate General of India, Sittwe invites quotation from authorised dealers/contractors, reputed, experienced and financially sound companies, firms ("The Vendor") for supply, installation, commissioning of Closed Circuit Television (CCTV) Camera System and other accessories at the Chancery building of the Consulate. The Cameras will be installed in the reception area, areas surrounding the building and the perimeter area.

2. The representatives of interested vendors should visit the site with prior appointment and submit their proposals/ rate quotations along with complete layout plan. Interested vendors may submit one or more quotations separately for the different make/brand of CCTV Camera system they offered.

3. Important dates are as below:

Date of publishing NIT	:	05.06.2018
Last date of submission of Quotation	:	1:00 PM on 05.07.2018
Date of opening of Quotation	:	3:00 PM on 05.07.2018

4. A brief terms & conditions, scope of work, technical specification and proforma for submission of quotations are enclosed. The vendor shall sign on every page of the document and submit their quotation, complete in all respect to the Head of Chancery, Consulate General of India, No. 4, Myin Pying Kwin Street, Pyi Daw Thar Quarter, Sittwe, Myanmar (hoc.sittwe@mea.gov.in). The tender documents can be downloaded from the website www.cgisittwe.gov.in, www.mea.gov.in, www.embassyofindiayangon.in and www.eprocure.gov.in.

6. The right of acceptance of tender(s) will rest with Competent Authority. Also, the Consulate is not bound to accept the lowest tender and reserves the right to reject or partially accept any or all the tender(s) received without assigning any reasons thereof.

Sd/-
(Rajesh Kumar)
Head of Chancery

Letter for Submission of tender

Dated _____,2018

To,

Head of Chancery
Consulate General of India
Sittwe, Rakhine State

Ref: Supply and Installation of Closed Circuit Television System (CCTV) at the
Chancery building of the Consulate.

Dear Sir,

Having examined the tender document relating to the Supply and Installation of Closed Circuit Television System (CCTV), we hereby submit our offer for the supply of the proposed items in accordance with terms and conditions and confirm our acceptance to execute the order within the time period specified in the tender document, at the rates quoted by us in the accompanying Technical & Financial Bid.

We further confirm that –

- i. We have successfully executed orders of similar nature and we have sufficient experience and financial strength in handling orders of this value.
- ii. We have sufficient qualified manpower and necessary materials and after sales support to execute the order efficiently in the specified time schedule.
- iii. The quoted rates shall be valid not less than 90 days from the date of opening of quotation.
- iv. We further confirm that all chapters of the tender documents have been read, understood and signed and there is no deviation/discrepancy.
- v. We agree to accept the extension order up to 100% quantity within three months of the issue of the order.

Signature of the Bidder
With stamp and date

Consulate General of India
Sittwe

No. Sit/Adm/885/04/2017

June 05, 2018

1.0 GENERAL

1.1 The CCTV system shall be used to monitor and record the data of the visitors coming from entry Gate of the Chancery, reception area and surrounding areas of the building and perimeter area. The vendor shall study the specifications and satisfy himself thoroughly and shall take full responsibility of the smooth, reliable and safe working. The representative of the vendor should visit the Consulate (herein referred as 'the site') prior to placing its bids for satisfying himself for supply of requisite items essential for smooth functioning of the system. Site can be inspected between 10 AM to 5 PM on working days till 04.07.2018. No transportation allowance or any other incidentals shall be payable by the Consulate to any out-station vendor on account of initial site visit. However, transportation charges and other incidentals in respect of technician(s), if any, for final installation may be included in the quotation.

1.2 All items of instrument shall be completed in all respects and any instrument not covered in the specification but essential for proper installation, operation and maintenance of the instrument shall be included by the vendor in his offer and the reasons for such inclusion shall be clearly stated.

2.0 SCOPE OF WORK

2.1 The scope of work includes supply, installation and commissioning of CCTV System in accordance with the design & specifications given in "**Annexure I Technical Bid A. TECHNICAL SPECIFICATIONS OF THE SECURITY SURVEILLANCE SYSTEM**". In addition, the vendor will also undertake the maintenance of the complete system.

2.2 Supply of necessary spares.

2.3 Packaging, forwarding, transport, insurance, loading, unloading, precaution against damage during transit etc.

2.4 Performance Guarantee.

2.5 Two sets of operation and maintenance manuals.

2.6 Test Certificate: Vendor shall provide all necessary test certificates.

3.0 SAFETY

3.1 All equipment items shall be complete with approved safety devices, wherever a potential hazard to personnel exists, and with provision for safe access to personnel to and around the instrument for operational and maintenance functions.

4.0 TIME FOR COMPLETION

4.1 The vendor shall complete supply, installation and commissioning of the instrument within 2 months of placing the Purchase Order or the timeline specified by the Consulate.

5.0 TEST AND INSPECTION

5.1 Inspection of the equipment will be done at the Consulate.

5.2 The vendor shall demonstrate all the features of the equipment mentioned in the technical specification.

5.3 The vendor is solely responsible for installation, commissioning and making the complete system operational at user's site.

6.0 OPERATION CONDITIONS

6.1 All equipment shall be designed for smooth, efficient and trouble free operation in tropical humid climate of 45° C ambient and a humidity of 90% to 150%.

6.2 In cases where the offer deviates from the specification, the vendor shall indicate clearly in his offer the specification proposed by him along with details thereof and the reasons for the deviation. Each exception to the specification or other parts of the tender document shall be listed separately by the vendor. If exceptions are not clearly listed they will not be considered by the Purchaser later.

7.0 DOCUMENTS

7.1 The vendor shall supply the hard and soft copy of Operation and Maintenance manual in duplicate. All necessary literature giving complete technical details shall be provided. He should also provide the test certificates given by manufacturer.

7.2 The vendor shall provide the original DVD/CD of all the software used for operating the system.

8.0 INSTALLATION & COMMISSIONING

8.1 It is to be noted again that supply, installation and commissioning of the system with all accessories, auxiliaries, and any item not covered in the specification but essential for proper installation, operation and maintenance of the CCTV System shall be included and executed by the vendor.

8.2 The supply will not be deemed complete until the commissioning trial of the whole system is carried out by the vendor at the site successfully.

12.0 PERFORMANCE AND GUARANTEE (P. G.)

12.1 All necessary tests shall be carried out at the site by the vendor to demonstrate whether performance of the instrument conforms to the relevant standards and specifications and meets the functional requirement indicated in the specification.

13.0 WARRANTY

13.1 The warranty period for the equipment will commence from the date of commissioning of the entire system and not from the date of delivery or installation.

13.2 The vendor shall provide guarantee for the entire system for a period of 12 months from the date of commissioning or for the duration of OEM warranty period whichever is longer.

13.3 The time period for product warranty will be the same as the service warranty.

13.4 The vendor shall be responsible for routine and breakdown maintenance of the equipment during warranty period.

13.5 It is desired that the winning vendor/firm will enter into an Annual Maintenance Contract (AMC) for a period of 3 years, commencing after the expiry of the initial service warranty, for maintaining the installed system.

14.0 PAYMENT TERMS

14.1 The payment will be released only after receipt, satisfactory installation/commissioning of the equipment in question and in good condition in the Consulate.

15.0 CAPABILITY AND EXPERIENCE

15.1 The vendor shall have executed at least two (2) similar kind of work within last 3 years. The vendor shall submit along the offer the reference list of the similar work. Offers received without the reference list may be rejected.

16.0 TRAINING

16.1 Vendor shall provide necessary onsite training at the Consulate about the working of CCTV System and the relevant software.

17.0 QUOTATION

17.1 Interested vendors may submit one or more quotations separately for the different make/brand of CCTV Camera system they offered.

17.2 Vendor can submit quotation in US Dollar or in Myanmar Kyats.

18.0 CLARIFICATIONS

18.1 For any clarification and appointment for site visit, the vendor may the Consulate by e-mail (hoc.sittwe@mea.gov.in/ adm.sittwe@mea.gov.in) and Tel. No. +95-43-2022918, 2022919, 2022076.

19.0 LAST DATE OF RECEIPT OF TENDER

19.1 Tender will not be accepted if they are received after the due date and time as specified in the quotations letter i.e. **on 05/07/2018 1:00 P.M.**

19.2 The vendor shall be required to submit the complete layout plan before executing the work/ submit the layout plan with the Financial Bid.

20.0 OPENING DATE OF TENDER

20.1 The tender will be opened on **05/07/2018 3:00 P.M.** in the Consulate. The Technical Bids (**Annexure I**) will first be evaluated and only vendors who qualified in the Technical Bids will only be considered for further evaluation of Financial Bids (**Annexure II**).

21.0 CONSULATE GENERAL OF INDIA, SITTWE RESERVE THE RIGHT

21.1. The right of acceptance of tender(s) will rest with Competent Authority. Also, the Consulate is not bound to accept the lowest tender and reserves the right to reject or partially accept any or all the tender(s) received without assigning any reasons thereof.

Annexure I
Technical Bid

A. TECHNICAL SPECIFICATIONS OF THE SECURITY SURVEILLANCE SYSTEM

DEVICE/ EQUIPMENT	PARTICULARS	MAKE
IP CCTV Camera	2 to 4 MP Dome Varifocal/ Bullet Varifocal/ High Speed IP PTZ	Bosch/ Honeywell/ Pelco/ Panasonic/ Sony/ Samsung
Network Video Recorder	32 Channel, third-party network cameras supported, up to 5 Megapixels resolution recording, HDD quota and group management	Bosch/ Honeywell/ Pelco/ Panasonic/ Sony/ Samsung
Surveillance-Optimised Storage	4 TB HDD	Seagate, WD, LG
POE Switch	16 GE + 2 SFP port	Cisco/HP/ Alcatel-Lucent/ Any reputed brand
Monitor	43" LCD monitor, 4k display, HDMI, USB 3.0, Ethernet	Sony
CAT 6a UTP Cable	Enhanced performance cable for transmission of high speed data, digital and analogue voice and video (RGB) signals on LANs	Reputed brand
PVC Conduit, Trunking + Accessories	Adaptable to standard concealed wiring system as per IS: & BS: Virgin Suspension grade K-67 PVC.	Reputed brand

Minimum Specifications for the Proposed CCTV Cameras

2-4 Megapixel H.265 Vandal Proof Network Dome IR Camera		
KEY FEATURES		
<ul style="list-style-type: none"> - 0.008 Lux - H.265 High Efficiency Video Coding - Integrated Motorized Varifocal Lens (Auto focus) - Built-in ICR Filter for Day/Night switching - Built-in web server for IE/Firefox/Chrome/Safari preview - 3D-DNR, Privacy Masking and Motion Detection - Built-In efficient IR LEDs, IR distance up to 30m - Weather-proof IP-67 rated housing - Built-in 802.3af Compliant PoE - Support ONVIF Profile S 		
IP VIDEO SURVEILLANCE SOLUTION		
	DESCRIPTION	SPECIFICATIONS
CAMERA	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	Color: 0.008Lux@F1.2 , B/W: 0Lux with IR on
	WDR	Super WDR up to 120dB
	Lens	3.6mm
	Field of View	H78.4°~H26.2° (2.8~12mm)
	Shutter Time	1/100000s~1/5s
	IR Distance	Up to 30m
	Day & Night	ICR Filter Auto Switch
	Max Image Resolution	1920X1080
VIDEO	Frame Rate	20fps(2592x1520) 25fps(2304x1296) 25fps(1920x1080)
	Video Compression	H.265(HEVC) / H.264 / MJPEG
	Video Bit Rate	160Kbps~16Mbps(CBR/VBR Adjustable)
	Image Setting	Brightness/Contrast/Saturation/Sharpness
NETWORK	Ethernet	1*RJ45 10M / 100M Ethernet Port
	Network Storage	NAS(Support NFS, SMB/CIFS)
	Protocol	TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS,DNS,DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPNP, SIP, IPv6, PPPoE, VLAN
AUDIO	Audio Streaming	Built-in Microphone
	Audio Compression	G.711 and AAC
SYSTEM	Advanced Function	Motion Detection, Privacy Masking, Backlight Compensation, 3D-DNR, ROI
	SIP/VoIP Support	Yes, Voice & Video over IP
	Event Trigger	Motion Detection, Network Disconnection, etc.
	Event Action	FTP Upload/SMTP Upload/SIP Phone
	System Compatibility	ONVIF Profile S

GENERAL	Power Supply	PoE
	Power Consumption	2.5W MAX, 5.5W MAX (With IR on) {can be removed}
	Weather Proof	Up to IP67 Rating for Weather-resistant
	Certification	CE, FCC, Rohs

NETWORK BULLET IR CAMERA (FIXED)		
KEY FEATURES		
	DESCRIPTION	SPECIFICATIONS
CAMERA	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	Color: 0.008Lux@F1.2 , B/W: 0Lux with IR on
	WDR	Super WDR up to 120dB
	Lens	3.6mm
	Field of View	H78.4°~H26.2° (2.8~12mm)
	Shutter Time	1/100000s~1/5s
	IR Distance	Up to 30m
	Day & Night	ICR Filter Auto Switch
	Max Image Resolution	1920X1080
VIDEO	Frame Rate	20fps(2592x1520) 25fps(2304x1296) 25fps(1920x1080)
	Video Compression	H.265(HEVC) / H.264 / MJPEG
	Video Bit Rate	160Kbps~16Mbps(CBR/VBR Adjustable)
	Image Setting	Brightness/Contrast/Saturation/Sharpness
NETWORK	Ethernet	1*RJ45 10M / 100M Ethernet Port
	Network Storage	NAS(Support NFS, SMB/CIFS)
	Protocol	TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS,DNS,DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPNP, SIP, IPv6, PPPoE, VLAN
AUDIO	Audio Streaming	N/A
	Audio Compression	N/A
SYSTEM	Advanced Function	Motion Detection, Privacy Masking, Backlight Compensation, 3D-DNR, ROI
	SIP/VoIP Support	Yes, Voice & Video over IP
	Event Trigger	Motion Detection, Network Disconnection, etc.
	Event Action	FTP Upload/SMTP Upload/SIP Phone
	System Compatibility	ONVIF Profile S
	Power Supply	PoE
	Power Consumption	5.5W MAX, 9.5W MAX (With IR on) {can be removed}
	Weather Proof	Up to IP67 Rating for Weather-resistant

GENERAL	Certification	CE, FCC, Rohs
---------	---------------	---------------

NETWORK BULLET IR CAMERA (MOTORIZED)		
KEY FEATURES		
<ul style="list-style-type: none"> - 0.008 Lux - Super WDR up to 140 dB - H.265 High Efficiency Video Coding - Integrated Motorized Varifocal Lens (Auto focus) - Built-in ICR Filter for Day/Night switching - Built-in web server for IE/Firefox/Chrome/Safari preview - 3D-DNR, Privacy Masking and Motion Detection - Built-In efficient IR LEDs, IR distance up to 30m - Weather-proof IP-67 rated housing - Built-in 802.3af Compliant PoE - Support ONVIF Profile S 		
IP VIDEO SURVEILLANCE SOLUTION		
	DESCRIPTION	SPECIFICATIONS
CAMERA	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	Color: 0.008Lux@1.2 , B/W: 0Lux with IR on
	WDR	Super WDR up to 120dB
	Lens	Motorized 2.8 ~ 12mm
	Field of View	H78.4°~H26.2° (2.8~12mm)
	Shutter Time	1/100000s~1/5s
	IR Distance	Up to 30m
	Day & Night	ICR Filter Auto Switch
	Max Image Resolution	1920x1080
VIDEO	Frame Rate	20fps(2592x1520) 25fps(2304x1296) 25fps(1920x1080)
	Video Compression	H.265(HEVC) / H.264 / MJPEG
	Video Bit Rate	160Kbps~16Mbps(CBR/VBR Adjustable)
	Image Setting	Brightness/Contrast/Saturation/Sharpness
NETWORK	Ethernet	1*RJ45 10M / 100M Ethernet Port
	Network Storage	NAS(Support NFS, SMB/CIFS)
	Protocol	TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS,DNS,DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPNP, SIP, IPv6, PPPoE, VLAN
AUDIO	Audio Streaming	N/A
	Audio Compression	N/A
SYSTEM		
	Advanced Function	Motion Detection, Privacy Masking, Backlight Compensation, 3D-DNR, ROI
	SIP/VoIP Support	Yes, Voice & Video over IP

	Event Trigger	Motion Detection, Network Disconnection, etc.
	Event Action	FTP Upload/SMTP Upload/SIP Phone
	System Compatibility	ONVIF Profile S
GENERAL	Power Supply	PoE
	Power Consumption	5.5W MAX, 9.5W MAX (With IR on) <i>{can be removed}</i>
	Weather Proof	Up to IP67 Rating for Weather-resistant
	Certification	CE, FCC, Rohs

High Speed full HD PTZ Dome (36X) Camera			
KEY FEATURES		CAMERA	
<ul style="list-style-type: none"> - 2-3 MP Resolution - 36x Optical Zoom - 5-120 mm Focal Length - 255 Preset Position - 360 Consinuous Rotation - 8 Cruise Track - 4 Pattern Track 			
Sl.No	Description		Specification
1.	Signal model		PAL / NTSC
2.	Image Sensor		1/1.8" or better CMOS
3.	Effective pixel		2084(H)* 1536(V)
4.	Horizontal Resolution		2-3 MP
5.	Minimum Illumination		Colour-0.01 lux / B&W - 0.001 Lux
6.	S/N ratio		>60dB
7.	Backlight compensation		On/Off
8.	White balance		Auto
9.	Electronic shutter		PAL:1/25~1/100000s NTSC:1/30~1/100000s
10.	Focus length		5-120mm
11.	Optical focus		36x
12.	Focus system		Auto/Manual
13.	IR distance		150M
14.	IR light control		Intelligent control technology
15.	IR light angle		Infrared zoom matching technology
16.	IR light power		Auto setting
17.	IR on		Day/Night/Auto/Timing
18.	IR Life		30000 hours
19.	Horizontal range		360° Continuous rotation
20.	Vertical range	(-90°~0°)	
21.	Preset call speed	Max 200°/S	
22.	Manual call speed	0.01°~180°/S	

23.	Presets	255	SYSTEM
24.	Cruise track	8 groups, each group for 16 presets	
25.	Patrol tract	4 groups, each group record 3 mins	
26.	Video compression	H.265 Main Profile encoding ; MJPEG /JPEG Baseline encoding	
27.	Audio compression	G.711, G.726	
28.	Primary stream	2048*1536 25fps	
29.	Secondary stream	720P, VGA 25fps	
30.	Video bit rate	32Kbps-16Mbps continuously adjustable, support CBR / VBR	
31.	Alarm Input / Output	Yes 1/1	
32.	Network protocol	TCP/IP,UDP,RTP,RTSP,RTCP,HTTP,DNS,DDNS, DHCP,FTP,NTP,PPPOE,SMTP,UPNP	
33.	ONVIF support	Support	GENERAL
34.	Cooling Structure	Dustproof structure outside the circle	
35.	Protection level	IP66	
36.	Power supply / PoE	DC12V(4A)/PoE Supported	
37.	Certification	CE, FCC, RoHS	

Other Technical Specifications

32 CH NVR (4HDD)		
KEY FEATURES		
<ul style="list-style-type: none"> - P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place. - Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard. - Support for H.264+ encoding format streaming access and decoding output - Support megapixel HD network video preview, storage and playback - Support search, playback and backup by event - Support all channel image display on one screen at same time, support 4 channels' image display by mainstream and 4 channels playback - Support monitor PTZ on preview mode 		
S.No	DESCRIP-TION	SPECIFICATION
1	Operation System	Embedded LINUX system
2.	Dual Stream	Channel can set main stream and sub stream
3.	Video Standard	H.264+/H.264
4.	Monitoring Image Quality	4K / 5MP / 3MP / 2MP / 1.3MP / 1MP

5.	Image Motion Image	Each screen can set multiple detection areas and set 6-level sensitivity
6.	Recording Playback Quality	Any 4ch 8MP playback/9ch 5MP playback/16ch 2 MP playback simultaneously
7.	Recording Mode	Support manual, auto, dynamic detection, alarm trigger record mode
8.	Backup Way	Support U disk, USB mobile HDD, USB DVDRW, network storage and backup (Partly needs IPC Support)
9.	Operation Way	Mouse, Keyboard
10.	Local Login	Username and password
11.	Recording Storage	Local HDD, network
12.	Video Input (mode)	1) 32x(3840*2160)+sub[960*576]+4Ref.+4Play H.264+8M/ch 32ch 4K IP Camera 2) 32x(2592*1944)+sub[960*576]+4Ref.+9Play H.264+8M/ch 32ch 5MP IP Camera 3) 32x(1920*1080)+sub[960*576]+4Ref.+16Play H.264+4M/ch 32ch 2MP IP Camera
13.	Audio Input	32ch network audio input
14.	Video Output	1ch VGA+1ch HDMI
15.	Audio Port	1ch RCA output
16.	Network Port	1 RJ45, 10M/100M/1000M self-adaptive LAN
17.	RS485 Port	Full duplex standard 485 port
18.	USB Port	1USB 3.0 Port, 2 USB 2.0 ports
19.	Alarm Input / Output	4ch / 4ch
20.	HDD Port	4xSATA+1xE-SATAHDD Port
21.	Max Capacity	Each Port supports MAX 6 TB HDD
22.	Mobile Surveillance	Supported
23.	Certification	CE, FCC, RoHS

DATA SHEET FOR 16 GE + 2 SFP PORT POE SWITCH

Sl. No.	DESCRIPTION	SPECIFICATION
1	PoE Port	16*10/100/1000 port support IEEE802.3af/at
2	SFP port	Yes
3	PoE port output power	15.4W/30W IEEE802.3af/at
4	PoE power supply pins	Both ½+, 3/6- and 4/5+, 7/8-
5	Transmission distance	100 ~ 150m
6	Protocol standard	IEEE802.3af/IEEE802.3at

7	PoE type	End-span
8	Network standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
9	Network medium	10/100/1000Mbps 5 class and above non shielded twisted pair
10	Network Signal Distance	<150m
11	Switch capability	7.2Gbps
12	Forwarding Mode	Store and forward
13	Forwarding Rate	100Mbps:14880pps / 1000Mbps:14800pps
14	MAC Address	MAC address table 8K
15	Port function	Power priority mechanism, fast and forward, MAC IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
16	Indicator	Each port occupied 1 LINK/ACT.100Mbps POE Status Indicator, Whole power indicator
17	Working Temperature	-10° ~ 55° C
18	Input power	AC100-240V 50/60HZ
19	Whole power	250W

**Annexure I
Technical Bid**

B. GENERAL INFORMATION

1	Name and Address of the Bidder	
2	Contacts	
3	Telephones	
4	Mobile no.	
5	Fax	
6	E-mail	
7	Category of the Bidder (Whether company, partnership firm or Proprietary concern)	
8	Name of Chief Executive Officer and Telephone no.	
9	Year of Establishment	
10	Name and address of the Banker	
11	List of major Clients and the size of orders executed	

Note: Separate sheets may be attached wherever necessary.

Signature of the Bidder
Name
With stamp and date

**Annexure II
Financial Bid**

DEVICE/ EQUIPMENT	PARTICULARS	MAKE OFFERED	WARRANTY (IN MONTHS)	QUANTITY IN NOS.	RATE (PER UNIT)	AMOUNT (US\$/ MMK)
IP CCTV Camera	2 to 4 MP Dome Varifocal/ Bullet Varifocal/ High Speed IP PTZ	Bosch/ Honeywell/ Pelco/ Panasonic/ Sony/ Samsung		As per requirement (10-13 no.)		
Network Video Recorder	32 Channel, third- party network cameras supported, up to 5 Megapixels resolution recording, HDD quota and group management	Bosch/ Honeywell/ Pelco/ Panasonic/ Sony/ Samsung		1		
Surveillance- Optimised Storage	4 TB HDD	Seagate, WD, LG		4		
POE Switch	16 GE + 2 SFP port	Cisco/HP/ Alcatel- Lucent/ Any reputed brand		1		
Monitor	43" LCD monitor, 4k display, HDMI, USB 3.0, Ethernet with Wall mount	Sony		1		
CAT 6a UTP Cable	Enhanced performance cable for transmission of high speed data, digital and analogue voice and video (RGB) signals on LANs	Reputed brand		As per requirement		
PVC Conduit, Trunking + Accessories	Adaptable to standard concealed wiring system as per IS: & BS: Virgin Suspension grade K-67 PVC.	Reputed brand		As per requirement		
Any others						
TOTAL (In Figure)						

TOTAL IN WORDS:

- Note:
1. The Financial Bid shall not include any conditions attached to it and any such conditional financial proposal shall be rejected summarily.
 2. The total quoted price should include all travel cost, shipping charges and other administrative cost, if any, that may be incurred by the vendor as part of this project.
 3. Separate sheets may be attached wherever necessary.

Signature of the Bidder
Name
With stamp and date